



Safety Data Sheet dated 1/2/2018, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier

Mixture identification: Trade name:

ARCHI+ TADELAKT

Trade code: N756019

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use:

Premixed powder

1.3. Details of the supplier of the safety data sheet

Company:

NOVACÓLOR S.R.L Via U. Aldrovandi, 10 47122 Forlì (FC) - Italy -Tel. +39 0543 401840 Fax. +39 0543 414585

Competent person responsible for the safety data sheet: reach@novacolor.biz 1.4. Emergency telephone number Technical information: NOVACOLOR SRL +39 0543 401840 (Monday – Friday 8.00-12.00 ; 13.30-17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- Warning, Skin Irrit. 2, Causes skin irritation.
- ♦ Danger, Eye Dam. 1, Causes serious eye damage.
- Warning, Skin Sens. 1B, May cause an allergic skin reaction.
- Warning, STOT SE 3, May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements Hazard pictograms:



Danger Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

N756019/1

Page n. 1 of 9



P501 Dispose of contents / container in accordance with national regulations. Special Provisions:

None Contains

calcium hydroxide

White cement

Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards vPvB Substances: None - PBT Substances: None Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

- 3.1. Substances
 - N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 15% - < 20%	calcium hydroxide	CAS: EC: REACH No.:	1305-62-0 215-137-3 01- 2119475151 -45-XXXX	
>= 7% - < 10%	White cement	CAS: EC:	65997-15-1 266-043-4	 ⁽¹⁾ 3.8/3 STOT SE 3 H335 ⁽²⁾ 3.2/2 Skin Irrit. 2 H315 ⁽³⁾ 3.3/1 Eye Dam. 1 H318 ⁽¹⁾ 3.4.2/1B Skin Sens. 1B H317
>= 3% - < 5%	Lime (chemical), hydraulic	CAS: EC: REACH No.:	85117-09-5 285-561-1 01- 2119475523 -36-XXXX	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

N756019/1

Page n. 2 of 9



- 4.2. Most important symptoms and effects, both acute and delayed None
- 4.3. Indication of any immediate medical attention and special treatment needed In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media: Water.
 - Carbon dioxide (CO2).
 - Extinguishing media which must not be used for safety reasons:
 - None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under point 7 and 8.
 6.2. Environmental precautions Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed. Incompatible materials: None in particular.

N756019/1 Page n. 3 of 9



Instructions as regards storage premises: Adequately ventilated premises. 7.3. Specific end use(s) None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters calcium hydroxide - CAS: 1305-62-0 - OEL Type: EU - TWA(8h): 1 mg/m3 - STEL: 4 mg/m3 - Notes: Respirable fraction - OEL Type: ACGIH - TWA(8h): 5 mg/m3 - Notes: Eye, URT and skin irr White cement - CAS: 65997-15-1 - OEL Type: ACGIH - TWA(8h): 1 mg/m3 - Notes: (E,R), A4 - Pulm func, resp symptoms, asthma Lime (chemical), hydraulic - CAS: 85117-09-5 - OEL Type: EU - TWA(8h): 1 mg/m3 - STEL(15min): 4 mg/m3 **DNEL Exposure Limit Values** calcium hydroxide - CAS: 1305-62-0 Worker Professional: 4 mg/m3 - Consumer: 4 mg/m3 - Exposure: Human Inhalation -Frequency: Short Term, local effects Worker Professional: 1 mg/m3 - Consumer: 1 mg/m3 - Exposure: Human Inhalation -Frequency: Long Term, local effects White cement - CAS: 65997-15-1 Worker Professional: 0.001 mg/l - Exposure: Human Inhalation **PNEC Exposure Limit Values** calcium hydroxide - CAS: 1305-62-0 Target: Fresh Water - Value: 0.49 mg/l Target: Marine water - Value: 0.32 mg/l Target: Microorganisms in sewage treatments - Value: 3 mg/l Target: Soil (agricultural) - Value: 1080 mg/kg Lime (chemical), hydraulic - CAS: 85117-09-5 Target: Fresh Water - Value: 490 µg/l Target: Soil (agricultural) - Value: 1080 mg/l 8.2. Exposure controls Eye protection: Use close fitting safety goggles, don't use eye lens. Protection for skin: Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use respiratory protection where ventilation is insufficient or exposure is prolonged. Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

. Information on basic physical an	a onennoar prop
Appearance:	powder
Colour:	white
Odour:	odourless
Odour threshold:	N.A.
pH:	11 - 14
Melting point / freezing point:	N.A.



Initial boiling point and boiling Solid/gas flammability:	g range: N.A.	N.A.	
Upper/lower flammability or e	explosive lin	nits:	N.A.
Vapour density:	N.A.		
Flash point:	N.A.		
Evaporation rate:	N.A.		
Vapour pressure:	N.A.		
Relative density:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient (n-octand	ol/water):	N.A.	
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
Viscosity:	N.A.		
Explosive properties:	N.A.		
Oxidizing properties:	N.A.		
9.2. Other information			
Miscibility:	N.A.		
Fat Solubility:	N.A.		
Conductivity:	N.A.		
Substance Groups relevant p	properties	N.A.	

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid Stable under normal conditions.
- 10.5. Incompatible materials None in particular.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Toxicological information of the product: **ARCHI+ TADELAKT** a) acute toxicity Not classified No data available for the product b) skin corrosion/irritation The product is classified: Skin Irrit. 2 H315 c) serious eye damage/irritation The product is classified: Eye Dam. 1 H318 d) respiratory or skin sensitisation The product is classified: Skin Sens. 1B H317 e) germ cell mutagenicity Not classified No data available for the product f) carcinogenicity Not classified No data available for the product g) reproductive toxicity Not classified No data available for the product

N756019/1 Page n. 5 of 9



h) STOT-single exposure The product is classified: STOT SE 3 H335
i) STOT-repeated exposure Not classified
j) aspiration hazard Not classified
k) data available for the product
j) aspiration hazard
k) data available for the product
Toxicological information of the main substances found in the product: calcium hydroxide - CAS: 1305-62-0
a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 2500 mg/kg

- SECTION 12: Ecological information
 - 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ARCHI+ TADELAKT

Not classified for environmental hazards No data available for the product

calcium hydroxide - CAS: 1305-62-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 50.6 mg/l - Duration h: 96 - Notes: tap water Endpoint: LC50 - Species: Fish 457 mg/l - Duration h: 96 - Notes: see water Endpoint: EC50 - Species: Daphnia 49.1 mg/l - Duration h: 48 - Notes: tap water Endpoint: LC50 - Species: Daphnia 158 mg/l - Duration h: 96 - Notes: see water Endpoint: EC50 - Species: Algae 184.57 mg/l - Duration h: 72 - Notes: tap water Endpoint: NOEC - Species: Algae 48 mg/l - Duration h: 72 - Notes: see water

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 32 mg/l - Duration h: 96

d) Terrestrial toxicity:

Endpoint: NOEC 2000 mg/kg - Notes: macroorganism

- Endpoint: NOEC 12000 mg/kg Notes: microorganism
- e) Plant toxicity:

Endpoint: NOEC 1080 mg/kg - Duration h: 21 - Notes: days

- 12.2. Persistence and degradability
 - N.A.
- 12.3. Bioaccumulative potential
- N.A.
- 12.4. Mobility in soil N.A.
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
 - None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

The product is not dangerous under current provisions of the Code of International Carriage of

N756019/1

Page n. 6 of 9



Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations. 14.2. UN proper shipping name

- 4.2. UN proper snipping na N.A.
- 14.3. Transport hazard class(es)
- N.A. 14.4. Packing group
- N.A.
- 14.5. Environmental hazards N.A.
- 14.6. Special precautions for user limited quantity: N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) 2015/830 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: No restriction. Restrictions related to the substances contained: No restriction. Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive) Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 None 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

- H315 Causes skin irritation.
 - H318 Causes serious eye damage.
 - H335 May cause respiratory irritation.
 - H317 May cause an allergic skin reaction.

N756019/1 Page n. 7 of 9



Hazard class and hazard category	Code	Description
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Skin Sens. 1B	3.4.2/1B	Skin Sensitisation, Category 1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1B, H317	Calculation method
STOT SE 3, H335	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of
CAS:	Dangerous Goods by Road. Chemical Abstracts Service (division of the American Chemical Society).
CLP: DNEL:	Classification, Labeling, Packaging. Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
N756019/1	·

Page n. 8 of 9



KSt: LC50:	Explosion coefficient. Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.